



VPG

■ 标准品一览表

额定电压 (浪涌电压) (V)	标称容量 (μ F)	产品尺寸 Φ D×L(mm)	L.C. (μ A,2min)	Tan δ 120Hz	ESR (m Ω 100kHz)	额定纹波电流 (mA r.m.s/105°C100kHz)
6.3(7.2)	10000	16×17.5	7500	0.30	7	9200
6.3(7.2)	12000	16×19.5	7500	0.34	7	9650
6.3(7.2)	15000	16×21.5	7500	0.40	7	9950
6.3(7.2)	15000	18×19.5	7500	0.40	7	9650
6.3(7.2)	18000	18×21.5	7500	0.46	7	9950
10(11.5)	6800	16×17.5	7500	0.24	8	8600
10(11.5)	8200	16×19.5	7500	0.26	8	9000
10(11.5)	10000	16×21.5	7500	0.30	8	9300
10(11.5)	10000	18×19.5	7500	0.30	8	9000
10(11.5)	12000	18×21.5	7500	0.34	8	9300
16(18.4)	3900	16×17.5	7500	0.18	8	8600
16(18.4)	4700	16×19.5	7500	0.19	8	9000
16(18.4)	5600	16×21.5	7500	0.21	8	9300
16(18.4)	6800	18×19.5	7500	0.24	8	9000
16(18.4)	8200	18×21.5	7500	0.26	8	9300
25(28.8)	2200	16×17.5	7500	0.14	16	6000
25(28.8)	2700	16×19.5	7500	0.15	16	6400
25(28.8)	3300	16×21.5	7500	0.17	16	6550
25(28.8)	3900	18×19.5	7500	0.18	16	6400
25(28.8)	4700	18×21.5	7500	0.19	16	6550
35(41)	1800	16×17.5	7500	0.14	20	5450
35(41)	2200	16×19.5	7500	0.14	20	5700
35(41)	2700	16×21.5	7500	0.15	20	5950
35(41)	2700	18×19.5	7500	0.15	20	5700
35(41)	3300	18×21.5	7500	0.17	20	5950
50(58)	680	16×17.5	6800	0.12	30	4400
50(58)	820	16×19.5	7500	0.12	30	4650
50(58)	1000	16×21.5	7500	0.12	30	4800
50(58)	1200	18×19.5	7500	0.12	30	4650
50(58)	1500	18×21.5	7500	0.13	30	4800
63(73)	560	16×17.5	7056	0.12	30	4400
63(73)	680	16×19.5	7500	0.12	30	4650
63(73)	820	16×21.5	7500	0.12	30	4800
63(73)	820	18×19.5	7500	0.12	30	4650
63(73)	1000	18×21.5	7500	0.12	30	4800
80(92)	330	16×17.5	5280	0.12	30	4400
80(92)	390	16×19.5	6240	0.12	30	4650
80(92)	470	16×21.5	7500	0.12	30	4800
80(92)	560	18×19.5	7500	0.12	30	4650
80(92)	680	18×21.5	7500	0.12	30	4800
100(115)	180	16×17.5	3600	0.12	40	3850
100(115)	220	16×19.5	4400	0.12	40	4000
100(115)	270	16×21.5	5400	0.12	40	4150
100(115)	270	18×19.5	5400	0.12	40	4000
100(115)	330	18×21.5	6600	0.12	40	4150